

# WHITE PTFE TAPE ▼

White PTFE tape is an economical and used for all purpose



## PHYSICAL PROPERTIES:

<b>Thickness:</b>	0.075mm, 0.1mm, 0.2mm
<b>Width:</b>	12mm(1/2") 19mm(3/4") 25mm(1")
<b>Composition:</b>	100% pure PTFE
<b>Temp.Range:</b>	-400F to +500F (-240C to 260C)
<b>Pressure Rating:</b>	up to 3,000PSI
<b>Tensile Strength:</b>	8N/mm <sup>2</sup>
<b>Elongation:</b>	Min 25%
<b>Storage:</b>	Unlimited shelf life (less than 70F recommended)
<b>Flammability:</b>	Non-flammable

1. Low density: 0.20g/cm<sup>3</sup>---0.30g/cm<sup>3</sup>
2. Medium density: 0.30g/cm<sup>3</sup>---0.70g/cm<sup>3</sup>
3. High density: 0.70g/cm<sup>3</sup>---1.80g/cm<sup>3</sup>



Listed  
Seal material  
4tk8  
MH48783



High density PTFE TAPE according to MIL-T27730A, UL. Applied for all types of threaded fittings for passage of water potable and non-potable, most chemicals, oxygen, gasoline, natural gas, hydraulic and high-pressure lines.

With density <0,70g/cm<sup>3</sup> are applied for the sealing of threaded joints on systems for water, compressed air, cooling and steam systems and hydraulic systems. Applicable on all types of materials (iron, metal, plastic, fibre etc.).